

**This Page Is Inserted by IFW Operations  
and is not a part of the Official Record**

## **BEST AVAILABLE IMAGES**

**Defective images within this document are accurate representations of the original documents submitted by the applicant.**

**Defects in the images may include (but are not limited to):**

- **BLACK BORDERS**
- **TEXT CUT OFF AT TOP, BOTTOM OR SIDES**
- **FADED TEXT**
- **ILLEGIBLE TEXT**
- **SKEWED/SLANTED IMAGES**
- **COLORED PHOTOS**
- **BLACK OR VERY BLACK AND WHITE DARK PHOTOS**
- **GRAY SCALE DOCUMENTS**

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**




**(10) International Publication Number**  
**WO 00/59179 A1**

## PCT

- [Continued on next page]

**(57) Abstract:** An electronic device having a main body which includes a main surface having an input device for inputting information. The electronic device further includes a flip that is rotatably attached to the main body. The flip includes a front surface and a rear surface wherein the flip is rotatable between a closed position wherein the front surface is adjacent the main surface and an open position wherein the flip is up-standing relative to the main surface. In addition, the device includes front and rear displays which are located on the front and rear surfaces, respectively, for displaying information.



## ELECTRONIC DEVICE HAVING A REVERSIBLE DISPLAY

### Field of the Invention

This invention relates to electronic devices which utilize a display, and more particularly, to an electronic device such as a wireless telephone having a two sided and reversible display so as to enable a user to view a display when a cover, or flip, of the electronic device is closed.

### Background of the Invention

It is frequently desirable to reduce the size of a portable electronic device such as a wireless telephone so as to increase convenience and portability. Many phones of this type include an input device for inputting a telephone number or other data, a display for displaying data and a cover or flip. The flip may be rotatably attached to a main body of the phone such that when the phone is not in use, the flip may be rotated to a closed position wherein portions of the main body are concealed. In a first type of phone design, the display and input device are located in upper and lower portions, respectively, of the main body. Further, the flip is sized such that the input device, and not the display, is concealed when the flip is closed. In a second type of phone design, the display is located in the flip whereas the input device is located in the main body. In this configuration, the flip is folded over onto the input device when the flip is closed thus concealing the display and forming a clamshell design which is smaller in size than the first phone design.

Frequently, a liquid crystal display (LCD) or similar device is used to display information on a wireless telephone. Such displays include a liquid crystal material which is positioned between front and rear glass plates to form an LCD cell. A surface treatment is applied to an inner surface of each glass plate such that molecules in the liquid crystal material near each inner surface align in the direction of the surface treatment. In LCDs known as twisted nematic LCDs, the inner surfaces are positioned orthogonal to each other such that a 90 degree twist is formed in the liquid crystal material.

FIGURE 2 is a view of the wireless telephone wherein the flip is in a closed position.

FIGURE 3 is a cross sectional view of the wireless telephone along section line 3-3 of FIGURE 1.

5 FIGURE 4 is a cross sectional view of the wireless telephone along section line 4-4 of FIGURE 2.

### Detailed Description of the Invention

While this invention is susceptible of embodiment in many different forms, there is shown in the drawings and will herein be described in detail specific embodiments, with the understanding that the present disclosure is to be considered as an example of the principles of the invention and not intended to limit the invention to the specific embodiments shown and described. In the description below, like reference numerals are used to describe the same, similar or corresponding parts in the several views of the drawing.

10 Referring to FIGURE 1, in conjunction with FIGURE 2, a wireless telephone 10 such as cellular or cordless phone having a reversible display in accordance with the present invention is shown. Although the present invention is described in relation to phones, it is noted that the present invention may also be utilized in conjunction with other electronic devices such as personal digital assistants (PDAs), cameras, pagers, personal computers, radios, recording and/or playback devices, calculators, televisions and others.

15 The phone 10 includes a main body 12 having a microphone 14, an input device 16 such as a touch sensitive device, touch screen, pointing device, mouse pointer, keypad and the like for inputting phone numbers or other data. In addition, the main body 12 may include a selection mechanism 18 for selecting stored information such as phone numbers, an antenna 11, accessory connector 15, battery, circuit boards and other components typically used for providing phone functionality. The phone 10 further includes a cover or flip 20 having a front surface 22 and a rear surface 24. The front surface 22 includes a speaker 26 and a front display 28 which serves to

20

25

circuitry associated with the phone 10 causes the rear light source 44 to be turned on and the front light source 42 to be turned off. Light 52 generated by the rear light source 42 is captured by the light gathering end 46 of the rear optical guide 40. The rear optical guide 40 then directs the light 52 toward the rear display 30. This serves to backlight the front display 28, thus  
5 improving visibility of the front display 28. In addition, it is noted that the LCD 36 may be a transflective LCD.

Referring to FIGURE 4, a cross sectional view along section line 4-4 of FIGURE 2 is shown. As previously described, the front surface 22 is adjacent the main body 12 when the flip 20 is moved to the closed position, thus concealing the front display 28. In addition, as also  
10 previously described, the inverted image 34 is displayed on the rear display 30 when the flip 20 is moved to the closed position. When this occurs, circuitry associated with the phone 10 causes the front light source 42 to be turned on and rear light source 44 to be turned off. Light 54 generated by the front light source 42 is then captured by the light gathering end 46 of the front optical guide 38 and directed toward the front display 28. As such, the direction of the  
15 illumination used for backlighting is reversed relative to that which occurs when the flip 20 is in the open position. This serves to backlight the rear display 30, thus improving visibility of the rear display 30 when the flip 20 is in the closed position.

Referring back to FIGURE 3, the flip 20 may further include a movable light inhibiting element 56, such as a door, which is positioned so as to cover and uncover the rear aperture 50 when the flip 20 is in the open and closed positions, respectively. In FIGURE 3, the element 56  
20 is shown covering the rear aperture 50. In this position, the element 56 shields the rear display 30 from outside light 58, thus further improving visibility of the front display 28 when the flip 20 is in the open position. Referring to FIGURE 4, the element 56 may then be moved away from the rear aperture 50 to enable viewing of rear display 30 when the flip 20 is in the closed  
25 position.

Alternatively, the light blocking element 56 may be a passive or active light filter that is stationary. In this configuration, the light filter is adapted to absorb or redirect light incident on the rear display 30 so as to improve visibility of the front display 28 when the flip 20 is in the open position. The light filter may also be adapted to let light through to allow viewing of the

**What Is Claimed Is:**

1. An electronic device, comprising:  
a main body having a main surface which includes an input device for inputting data;  
a flip rotatably attached to said main body, said flip having a front surface and a rear surface wherein said flip is rotatable between a closed position wherein said front surface is adjacent said main surface and an open position wherein said flip is upstanding relative to said main surface; and  
front and rear displays located on said front and rear surfaces, respectively, for displaying information.
2. The device according to claim 1, wherein said front display displays information which is substantially similar to that displayed on said rear display.
3. The device according to claim 1, wherein said information is related to operation of said electronic device.
4. The device according to claim 1, wherein said front and rear displays are backlit.
5. A portable electronic device, comprising:  
a main body having a main surface which includes an input device for inputting data;  
a flip rotatably attached to said main body, said flip having a front surface and a rear surface, wherein said flip is rotatable between a closed position wherein said front surface is adjacent said main surface and an open position wherein said flip is upstanding relative to said main surface;  
a front display located on said front surface for displaying information when said flip is in said open position, wherein said front display is concealed when said flip is in said closed position; and

flip is in said open position, wherein said front display is concealed when said flip is in said closed position;

a rear display located on said rear surface for displaying information when said flip is in said closed position;

a front backlight device for backlighting said rear display when said flip is in said closed position;

a rear backlight device for backlighting said front display when said flip is in said open position; and

a door located in said flip, said door being movable between a closed position wherein said door covers said rear display when said flip is in said open position and an open position wherein said door does not cover said rear display when said flip is in said closed position.

13. The device according to claim 12, wherein said front and rear backlight devices include a cold cathode fluorescent tube or a hot cathode fluorescent tube.

14. The device according to claim 12, wherein said front and rear backlight devices include a light emitting diode (LED).

15. The device according to claim 12, wherein said front and rear backlight devices are located adjacent rear and front optical guides, respectively.

16. The device according to claim 12, further including a liquid crystal display (LCD) which includes said front and rear displays.

17. The device according to claim 16, wherein said LCD is positioned between said front and rear optical guides.

1/2




FIG. 2

FIG. 1



# INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 00/08253

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 7 H04M1/02 G06F1/16

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G06F H04M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 98 38822 A (MOTOROLA INC) 3 September 1998 (1998-09-03) column 2, line 15 -column 3, line 30; figures 1-3	1-3, 5-8
A	—	12
X	US 5 796 577 A (OUCHI GENJIRO ET AL) 18 August 1998 (1998-08-18) column 1, line 55 -column 2, line 42; figure 1	1-3, 5-7
X	DE 40 19 755 A (TRIUMPH ADLER AG) 9 January 1992 (1992-01-09) abstract; figure 1	1-4
A	—	5-10, 12
	-/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*&\* document member of the same patent family

Date of the actual completion of the international search

11 July 2000

Date of mailing of the international search report

19/07/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

de Biolley, L

# INTERNATIONAL SEARCH REPORT

Information on patent family members

Int. Jonal Application No

PCT/US 00/08253

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9838822 A	03-09-1998	US 5896575 A BR 9714549 A CN 1247675 A EP 0963668 A	20-04-1999 08-02-2000 15-03-2000 15-12-1999
US 5796577 A	18-08-1998	JP 10207574 A	07-08-1998
DE 4019755 A	09-01-1992	NONE	
GB 2343324 A	03-05-2000	DE 19952682 A	11-05-2000